



25A6, 25A6-GT/G

POWER AMPLIFIER PENTODE

~~25A6~~
~~25A6-GT/G~~

Heater	Coated Unipotential Cathode	
Voltage	25	a-c or d-c volts
Current	0.3	amp.
	25A6	25A6-GT/G
Direct Interelectrode Cap.	▲	
Grid to Plate	0.2	μf
Input	8.5	μf
Output	12.5	μf
Maximum Overall Length	3-1/4"	3-5/16"
Maximum Seated Height	2-11/16"	2-3/4"
Maximum Diameter	1-5/16"	1-5/16"
Bulb	Metal Shell, MT-8	T-9
Base	{ Small Wafer Octal 7-Pin	{ Intermed. Sh. Octal 7-Pin
Basing Designation	7S	G-7S
Pin 1 { 25A6, Shell 25A6-GT/G, No Con.		Pin 5 - Grid
Pin 2 - Heater		Pin 7 - Heater
Pin 3 - Plate		Pin 8 - Cathode, Grid #3
Pin 4 - Screen		
Mounting Position		Any



BOTTOM VIEW

Maximum Ratings Are Design-Center Values AMPLIFIER

Plate Voltage	160 max. volts
Screen Voltage	135 max. volts
Plate Dissipation	5.3 max. watts
Screen Dissipation	1.9 max. watts

Typical Operation and Characteristics- Class A₁ Amplifier:

Plate Voltage	95	135	160	volts
Screen Voltage	95	135	120	volts
Grid Voltage *	-15	-20	-18	volts
Peak A-F Grid Voltage	15	20	18	volts
Zero-Sig. Plate Current	20	37	33	ma.
Max.-Sig. Plate Current	22	39	36	ma.
Zero-Sig. Screen Current	4	8	6.5	ma.
Max.-Sig. Screen Current	8	14	12	ma.
Plate Resistance	45000	35000	42000	ohms
Transconductance	2000	2450	2375	μmhos
Load Resistance	4500	4000	5000	ohms
Total Harmonic Distortion	11	9	10	%
Max.-Sig. Power Output	0.9	2	2.2	watts

■ Heater-cathode bias should not exceed 90 volts d.c. as measured between negative heater terminal and cathode.

▲ With shell connected to cathode. Values are approximate.

* The d-c resistance in the grid circuit should not exceed 0.5 megohm with cathode bias. With fixed bias, the d-c resistance may be as high as 0.5 megohm for the 95-volt condition, but should be limited to 0.1 megohm for the 135-volt and 160-volt conditions.

Curves under Type 43 also apply to the 25A6 and 25A6-GT/G.

→ Indicates a change.

Mar. 20, 1943

RCA VICTOR DIVISION

RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY


DATA

25A6



25A6

AVERAGE PLATE CHARACTERISTICS



JAN. 8, 1940

RCA VICTOR DIVISION
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

92C-4559RI